

EIGHT-FOOT TYPE III MOVEABLE BARRICADE (MGS-02-11D)

**1.0 DESCRIPTION.** This specification covers eight-foot wide Type III Moveable Barricades.

**2.0 GENERAL.** The eight-foot wide Type III barricade shall consist of three horizontal panels mounted to supports in such a manner that the entire assembly is capable of remaining upright and entirely free standing.

**2.1 SUPPORT.** The support structure shall consist of a minimum of two uprights capable of keeping the panels securely attached in the designated arrangement shown in Figure 1. The uprights shall be mounted to a base capable of supporting the entire assembly while remaining completely portable.

**2.2 PANELS.** The panels shall consist of a substrate of high-density polyethylene, wood, or other approved material in the dimensions shown in Figure 1. Nominal dimensions will be allowed for dimensional lumber. MoDOT Type 4 retroreflective sheeting in accordance with Sec 1042 shall be applied as shown in Figure 1 to one side of each panel and in the reverse image on the opposite side of each panel.

**3.0 MASH CERTIFICATION.** The manufacturer shall provide written certification the eight-foot wide Type III barricade provided complies with this specification and with the requirements of MASH, Test Level 3 when deployed as follows:

- a) a stand alone device,
- b) a device with two lightweight warning lights,
- c) a device with a lightweight substrate sign,
- d) a device with two lightweight warning lights and a lightweight substrate sign, and
- e) a label on the post identifying MASH compliance.

**4.0 ACCEPTANCE.** Acceptance of eight-foot wide Type III barricades will be by certification and any tests deemed necessary by the department for compliance with this specification.

Figure 1:

EIGHT-FOOT WIDE TYPE III MOVEABLE BARRICADE

