




Debra M. Butchart

From: Debra M. Butchart
Sent: Friday, August 2, 2024 2:57 PM
To: BR
Subject: Bridge Advertisement (DSI 24-018) Concrete Diaphragm Width at Intermediate Bents

The EPG has been updated as described below:

Implementation Statement: **Effective immediately for all plans not yet submitted to Design**

(The Implementation Statement is a recommendation by the Development Section. The SPM is responsible for the level of implementation for any particular job.)

Revision Date	Items Revised	Description of Change
 Aug. 2024	EPG:  751.22.3.7 ;  751.21.3.6	Modified 751.21.3.6.1, note (e), by removing the edge distance requirement for the concrete diaphragm, which was dependent on beam cap stirrup size. Added guidance to seek SPM approval for making the concrete diaphragm flush with the beam cap.
	Bridge Standard Drawings: NA	
	MicroStation Cells: NA	Modified 751.22.3.7.1, SECTION A-A, by moving a dimension line for clarity.
	Std. Specifications: NA	Modified 751.22.3.7.1, note (c), to read the same as that for 751.21.3.6.1 note (c).
	Standard Plans: NA	
	Bridge Special Provisions: NA	

Follow links above for more information, or to view more details about this (or any) revision, use the [Revision Index Database](#), located under Completed Revisions on Development's Sharepoint page.

Instructions:

Under Tables (left-hand side) double-click on RevisionRecords.

Click on the link under the Effective Date to access documentation for the completed revision.

Debra (Debbie) Butchart

(formerly Debra Beckwith)

Structural Specialist

Development Section

Bridge Division

MoDOT- 105 West Capitol Ave

573-522-8718