From: <u>Debra M. Butchart</u>

To: BR

**Subject:** Bridge Advertisement (DSI 25-003) MSE Wall Clear Space Requirements.

**Date:** Friday, July 18, 2025 8:51:41 AM

The EPG has been updated as described below:

## **Implementation Statement:** Effective immediately for design process not started.

(The Implementation Statement is a recommendation by the Development Section. The SPM is responsible for the level of implementation for any particular job.)

| Revision Date    | Items Revised        | Description of Change                                |
|------------------|----------------------|--|
| <u>July 2025</u> | EPG:                 | EPG 751.24.1 revised to clarify clear space          |
|                  | 751.24.2.1; 751.50   | requirement between MSE wall and front face of the   |
|                  | Bridge Standard      | abutment beam (setback distance). For bridges        |
|                  | Drawings:            | longer than 200 feet, modify standard note E1.2b for |
|                  | NA                   | larger CIP pile size and use minimum 6" larger pipe  |
|                  | MicroStation Cells:  | spacer diameter than CIP pile.                       |
|                  | NA                   |  |
|                  | Std. Specifications: |  |
|                  | NA                   |  |
|                  | Standard Plans:      |  |
|                  | NA                   |  |
|                  | Bridge Special       |  |
|                  | Provisions:          |  |
|                  | NA                   |  |

Follow links above for more information (internal only).

## Debra (Debbie) Butchart

(formerly Debra Beckwith)
Structural Specialist
Development Section
Bridge Division
MoDOT- 105 West Capitol Ave
573-522-8718